

7300



Battery-Powered Riding Scrubber

- Over 300% more scrubbing with foam-based FaST™
- Dependable operation delivering a higher quality of cleanliness
- Reduced training time and increased productivity with intuitive controls and low-maintenance design



The Safe Scrubbing Alternative®

Superior performance for a consistently clean, safe workplace

The highly-productive, dependable 7300 scrubber creates clean, safe environments that meet the highest standards. Even in the harshest industrial conditions, the 7300 delivers legendary Tennant performance.

Maximize scrubbing productivity

Multiple scrub-head widths and powerful, large-capacity batteries deliver hours of productive, fume-free scrubbing time, and enable cleaning coverage rates up to 100,000 sq. ft./hr.

Reach a higher level of cleanliness every day

The 7300 tackles tough dirt, grime and grease with three down-pressure settings in addition to a SuperScrub™ mode, delivering the performance you need to meet your daily cleaning challenges.

Rely on long-lasting, worry-free operation

Superior engineering and non-corrosive Duramer™ construction keep the 7300 rust-free and available to scrub day after day, year after year.

The safest way to clean

The best way to meet the highest cleaning standards using 70% less solution, FaST foam cleans so well it not only captures existing soil, it also removes old, slippery detergent residues. The result is a cleaner, higher-traction floor that reduces your risk of slip-and-fall.



MUST-HAVE OPTIONS

Safe and efficient clean-out

With the positive drain control, empty and rinse the recovery tank quickly and easily when a floor drain is not directly accessible.

Extend your cleaning reach

Add an optional off-aisle power wand for greater flexibility in hard-to-reach areas.

Boost scrubbing power and productivity

Optional MaxPro™ 1200 scrub head provides continual edge cleaning and a 48-inch (1200 mm) scrub path.



FaST FLOORS ARE SAFER FLOORS

FaST is the only automatic scrubbing system certified to increase floor traction up to 21% by the National Floor Safety Institute, reducing the risk of slip-and-fall.

FaST foam cleans so well, it uses 70% less solution to remove existing soil, as well as old, slippery detergent residue resulting in clean, higher-traction floors.

With the self-contained FaST-PAK™, operators are safer, never handling chemicals.

FaST foam uses up to 70% less water and 90% less detergent – conserving water, reducing waste disposal, and making FaST the safest environmental choice.



A

Increase productivity and extend run time with large-capacity batteries housed in an easy-to-access compartment.

B

Reduce maintenance and maximize cleaning time with quick, easy brush and squeegee adjustments.

C

Exceptional pick-up of virtually all water and residue from an equal-traction parabolic squeegee.

D

Customize to meet specific cleaning needs with a choice of cylindrical or disc brushes, multiple path widths, and a wide variety of accessories.

E

Reduce training and maximize productivity with optional power steering and one-button, easy-to-operate power control panel.



GENUINE TENNANT PARTS, SUPPLIES & SERVICE

Foam-based FaST Key to Peak Productivity and Safety

Using an innovative foam-based detergent delivery system, scrubbers with FaST increase productivity, eliminate the need for operators to handle chemicals, and leave just-cleaned floors immediately dry and safe for traffic.

Genuine Tennant Parts Advantage

Operate your machine with confidence by choosing genuine Tennant parts. Only authentic Tennant parts are engineered in conjunction with Tennant equipment. For years of worry-free operation, accept only genuine parts and supplies.

Industry's Only Factory-Direct Service Network

Tennant offers the only factory-trained, locally based network of 400+ service techs dedicated to keeping your cleaning program up and running.

WARRANTY

All parts (excluding batteries) have a 24 month / 2,000 hours of operation warranty under normal use and service. On-site service labor coverage of warranty items for six (6) months.



FaST is the first and only automatic cleaning system certified by the NFSI to dramatically improve overall floor traction by up to 21%.

SEEING IS BELIEVING

See for yourself how the 7300 rider scrubber delivers clean, safe floors in your most challenging environments. For a demonstration or additional information, call **800.553.8033**.

7300 BATTERY-POWERED RIDING SCRUBBER

FEATURES

Scrubbing System

Cleaning path

MaxPro™ 1000 scrub head (standard)	40-inch	1020 mm
MaxPro 1200 scrub head (optional)	48-inch	1220 mm

Edge scrub reach

	5-inch	130 mm
--	--------	--------

Solution tank

	57 gallon	216 liter
--	-----------	-----------

Disc scrub head

Speed	320 rpm	320 rpm
-------	---------	---------

Down pressure weight (variable to)	500 lb	225 kg
------------------------------------	--------	--------

Brush diameter (2) MP1000	20-inch	510 mm
---------------------------	---------	--------

Brush diameter (3) MP1200	16-inch	410 mm
---------------------------	---------	--------

Brush motor (2) MP1000	1 hp	0.75 kW
------------------------	------	---------

Brush motor (2) MP1200	1 hp	0.75 kW
------------------------	------	---------

Cylindrical scrub head

Speed	500 rpm	500 rpm
-------	---------	---------

Down pressure weight (variable to)	500 lb	225 kg
------------------------------------	--------	--------

Brush diameter (2)	9-inch	230 mm
--------------------	--------	--------

Brush motor (2)	1.5 hp	1.2 kW
-----------------	--------	--------

Recovery System

Recovery tank	74 gallon	281 liter
---------------	-----------	-----------

Demisting chamber	17 gallon	65 liter
-------------------	-----------	----------

Vacuum fan speed	14,000 rpm	14,000 rpm
------------------	------------	------------

Vacuum water lift	65-inch	1655 mm
-------------------	---------	---------

Vacuum fans (2)	0.85 hp	0.65 kW
-----------------	---------	---------

Propelling System

Propel speed forward (variable to)	5.5 mph	8.8 km/h
------------------------------------	---------	----------

Propel speed reverse (variable to)	3.0 mph	4.8 km/h
------------------------------------	---------	----------

Propel motor	4.6 hp	3.5 kW
--------------	--------	--------

Gradeability

Transport at gross weight	8 deg/14%	8 deg/14%
---------------------------	-----------	-----------

Working (scrubbing)	6 deg/10.5%	6 deg/10.5%
---------------------	-------------	-------------

Machine Dimensions

Length	84-inch	2130 mm
--------	---------	---------

Width	45-inch	1140 mm
-------	---------	---------

Rear squeegee MP1000	51-inch	1295 mm
----------------------	---------	---------

Rear squeegee MP1200	59.5-inch	1510 mm
----------------------	-----------	---------

Height	57-inch	1445 mm
--------	---------	---------

With overhead guard	81.5-inch	2070 mm
---------------------	-----------	---------

Weight	1980 lb	895 kg
--------	---------	--------

With standard 500 Ah battery	3430 lb	1555 kg
------------------------------	---------	---------

Minimum aisle turn	92-inch	2335 mm
--------------------	---------	---------

Tennant

701 North Lilac Drive
P.O. Box 1452
Minneapolis, MN 55440-1452
800.553.8033
d: 763.540.1200
In Quebec: 514.335.6061
f: 763.513.2112
tennantco.com
info@tennantco.com