



FLOOR GRINDING SOLUTIONS

FOR A BETTER WAY OF WORKING

Husqvarna PG 280

The PG 280 is a single disc floor grinder that you can quickly convert for edge grinding on both sides. It efficiently grinds adhesives, paint, epoxy and spackle. With a grinding width of 11 in. it is suitable for small to medium concrete areas. It is available in both 1- and 3-phase versions. Designed to facilitate an ergonomic work position, it is easy and convenient to use. The machine is light and compact and therefore easy to transport and set-up.

Output power
 2.05 hp
 (As rated by the engine/motor manufacturer)

2 Grinding width **11 in**

Rated input power 2 hp

Phases1 ph



FEATURES







2.05 hp

Quick conversion to edge grinding

Easily removable lid covers and wheel setting enable quick conversion to edge grinding on both sides. No tools are required. Allows an upright work position.

Easy removal

Offers efficient grinding of adhesive, paint, epoxy and spackle.

Edge grinding

of adhesive residue, paint and spackle on medium-sized concrete areas.

Easy to transport and set-up

The machine is light and fits easily in any car thanks to the compact design and foldable frame and dividable parts.

SPECIFICATIONS



(As rated by the engin	ne/motor
manufacturer)	G 18
Rated input power	2 hp
Rated current	19 A
Voltage	100-120 \
Phases	1 ph
Pins	3-pin
Frequency	60 Hz

Output power

Dimension	Product size width Product size height Weight	16.5 in 39 in 154.3 lbs
	Grinding width	11 in
	Grinding disc speed min	0 rpm
Other Other	Grinding disc speed max	1150 rpm
	Direction of rotation	One Direction
	Number of grinding discs	1

