

**UNMATCHED  
PRODUCTIVITY  
FOR YOUR  
FACILITY**



Husqvarna®



**FACTORY  
CLEANING  
EQUIPMENT** INC.  
By **Jon·Don**

**DUST & SLURRY SOLUTIONS**

FOR A BETTER WAY OF WORKING



# Husqvarna S 36

The S 36 is a very powerful single-phase HEPA dust extractor to match Husqvarna grinding machines as well as small to mid-size scarifiers, shot blasters and handheld power tools. This professional dust extractor is designed to meet strict demands. Three large, commercial-grade vacuum motors provide plenty of power. Equipped with three independently tested and certified HEPA H13 filters and a massive cone-shaped pre-filter with over 4.5 m<sup>2</sup> of media. This results in superior dust collection, even of fine sanding and gypsum dust. Features include Jet Pulse pre-filter cleaning, hour counter and vacuum meter for filter control. The non-marking wheels are puncture free and lock at the front. The Longopac® bag hose system ensures simple, dust-free bag changes.



- Phases **1~**
- Air Flow, m<sup>3</sup>/h **600 m<sup>3</sup>/h**
- Rated input power **3.6 kW**
- Weight **63 kg**

## FEATURES



### Efficient filtration system

The three separate filtering stages result in longer working time between filter cleaning. The dust is filtered through a cyclone chamber, which separate the heaviest parts, up to 95% of the dust, before the washable main filter. The HEPA micro filters are individual tested and certified to capture 99.99% of the remaining silica dust in the respirable fraction (0.3µm).



### Easy and efficient filter cleaning

The Jet Pulse filter cleaning system ensures high continuous airflow thanks to easy and efficient cleaning of the conical main filter without opening the machine.

### Durable design

Corrosion-resistant steel clamps, welded frame with dust bag platform and durable steel handle make it ready to serve for many years.

### Easy to transport

The welded frame enables easy transportation by resting the machine on the frame.

## SPECIFICATIONS



**Motor**

Phases	<b>1~</b>
Voltage	<b>230 V</b>
Rated current	<b>15.7 A</b>
Max. vacuum	<b>280 mbar</b>
Rated input power	<b>3.6 kW</b>

Air Flow, m <sup>3</sup> /h	<b>600 m<sup>3</sup>/h</b>
Air requirement	<b>600 m<sup>3</sup>/h</b>
HEPA filters 99.99% at 0.3 microns	<b>3</b>
Max. vacuum	<b>280 mbar</b>
Water lift	<b>110 in</b>

### Other



**Dimensions**

Product size height	<b>1500 mm</b>
Product size length	<b>830 mm</b>
Product size width	<b>620 mm</b>
Weight	<b>63 kg</b>

Factory Cleaning Equipment, Inc. by Jon-Don  
**800-793-3790**  
[www.thesweeper.com](http://www.thesweeper.com)

